

Vacuum Units - Dry Blower

For Sale
Only

WOMVAC DB - 9000m³/hr @ 27"hg Dry Blower



Basic Specifications:

One versatile sucker! With a debris tank made of 250 grade steel and capable of carrying 10T, dry positive displacement blower, discharge and inlet silencers, vertical direct shift transfer case, bag house complete with 32 filters, powerful hydraulics for hydraulic lift arm, half rear door unlock and lift, and vacuum safety brake these units are ready to perform.

Features:

With a simple control panel, dual cyclone separators, direct driven dry blower, cab controls, you can't go past this for value for money and performance. Other specifications and options are available to suit your exacting needs or requirements. These units are designed for remote area versatility and brute power so bring-on the challengers!



Units are currently working in WA, QLD, VIC and NSW - viewing and customer reference can be arranged by calling (08) 9434 6622

WOMVAC Dry Blower 08

Dry Blower vacuum truck

Technical specifications/features:

PUMP

- Positive displacement air cooled Hison SIAV 8702 roots type dry blower
- Volume – 9000 m³/hr at the max speed (2000rpm)
- Vacuum – Rated @ 27" Hg (Inches of Mercury)
- 225 kW required drive

DRIVE

- Powered by the main truck engine direct coupled via an Omsi transfer case and drive shaft

CONTROL PANEL

- Hydraulic control panel on passenger side of vehicle
- Vacuum gauge
- Hour meter
- Working lights & switch

DEBRIS TANK

- 10m³ capacity
- Mild steel construction, with RHS stiffening bands
- Electric Tank vibrator to assist with waste removal
- Half or Full opening hydraulic rear door
- Specifications to suit your boom requirements (fixed, swivel or otherwise)
- Surface treatment to include sandblast to Grade 2.5, zinc rich primer, Poly U top coat to industry recognized DFT

FILTRATION SYSTEM

- Main tank primary separation
- Twin cyclone secondary separation
- Final bag house filtration through 32 pleated bag filter cartridges complete with automatic pulse to assist bag life

SAFETY FEATURES

- Vacuum Release
- Emergency Stop Switches
- Debris Tank tipping safety leg

Please note the photos shown on the opposite page are for the model specifications listed above however WOMA will work with you on your specific requirements if requested.